Test Equipment for Marine Hose NDT Recertification & Service Life Destructive Tests



HELPING MAINTAIN OCIMF COMPLIANCE



Range of Marine Hoses

Suitable to test bonded marine hoses manufactured in accordance with OCIMF 1991 and GMPHOM 2009. Up to 24" diameter, 40ft long and 21 bar rated pressure as standard. Higher pressures catered for.

Range of Non-Destructive & Destructive Tests

For recertifying used and >5 year old unused hoses prior to service as per OCIMF publication, Single Point Mooring Maintenance & Operations Guide, (SMOG) 3rd Edition 2015.

Testing to meet the requirements of section 5.7 & 5.8 of SMOG i.e.

- Hydrostatic routine pressure test
- Vacuum test
- Electrical tests
- Hydrostatic burst pressure test

Efficient Operation:

Pumps sized to reach required hydro and vacuum pressures quickly.

Hydro pump can pressurise up to four 24" hoses at once.

Vacuum pump can reach required vacuum pressure within <15 minutes.

Compact & Lightweight:

Portable units that can be manually relocated around site without the need of a forklift.

Flexible Design:

Electrical or diesel or air driven designs available to suit local supply.

Digital or analogue gauges.

Integrated chart recorder.

Ancillary Equipment:

Pressure blind flange, vacuum test blinds, water filling pumps, compressor, hand tools, tool chest etc..

Quality: Made in UK.

Allied Marine Logistics Limited 3rd Floor, 207 Regent Street London, W1B 3HH United Kingdom

Tel: +44 (0)20 3355 8781 Fax: +44 (0)20 3051 5716

www.almarlog.co.uk